



HAILEIENERGY.COM

Basic Parameters	1-module	2-module
Argument	6KW+5KWh	6KW+10KWh
Output power	5000W	6000W
Input voltage range	220-240VAC	220-240VAC
Output voltage	230VAC+5%	230VAC+5%
Output frequency	50Hz ± 0.3Hz/60Hz ± 0.3Hz	50Hz ± 0.3Hz/60Hz ± 0.3Hz
Battery type	LiFeP04 battery	LiFeP04 battery
Depth of discharge	51.2V100Ah	51.2V100Ah
Number of batteries	1	2
Charging current	80A	80A
Output waveform	Pure sine wave	Pure sine wave
Output efficiency	> 93%	> 93%
Weight	About 100Kg	About 160Kg
Dimension	600*228*880	600*228*1280
Protection class	IP65	IP65
Cooling mode	Air cooling	Air cooling
Operating temperature range	0-55°C	0-55°C
Storage temperature	-15-40 °C	-15-40°C
Relative humidity	0-90%RH	0-90%RH
Certification standard	CE	CE

APP L-P

Real-time monitoring and Remote upgrade



Cycle Life Up to 6000+ cycles



IP65
Indoor and outdoor installation options



Equipped with advanced BMS , with voltage, current, power, temperature, shunt trip and other protection functions



With active balancer Extend the battery service life

Application scope







Household Company Hotel

PAGE 30 PAGE 31